



EVO Gateway

TRANSACTION RESULT CALL v 4.0 April 10, 2020

Notice: The information in this document is confidential and proprietary to EVO and is only intended for use by merchant customers of EVO, internal staff, and authorised business partners of EVO.

This document is protected by copyright restricting its use, replication in any format, and distribution. No part of this document may be reproduced in any form by any means without the express permission of EVO.

EVO reserves the right to amend, delete or add to the contents of the document, at any time, and to make improvements and/or changes to the products and/or programmes described in this document.

Every reasonable attempt will be made to ensure that the contents of the document are accurate, and a true reflection of the products and programmes described herein. However, EVO will not be held liable for any inaccuracies of any nature, however communicated by EVO.

EVO and other trademarks are trademarks or registered trademarks of their respective owners.

All other product names mentioned in this document are the trademarks of their respective owners.

© EVO 2017



Table of Contents

Document Purpose 2

1 Transaction Result Call 3

Document Purpose

The purpose of this document is to describe the TRANSACTION RESULT CALL API Operation to enable merchant developers to integrate their webpages with the EVO Gateway. Refer to the *EVO Gateway – 0 – Overview document* for how this API Operation is used in the merchant processes.

A Transaction Result Call is a secure, server-to-server transmission between the EVO Gateway and the merchant’s server. When an API operation is completed (successfully or not), a Transaction Result Call is sent to inform the merchant about the result and the status of the transaction.

The Transaction Result Call is sent to the URL that is provided in *merchantNotificationUrl* in the Session Token Request of the Authorise or Purchase API Operation (see *EVO Gateway – 2 – AUTH-PURCHASE-VERIFY – Direct API* or *EVO Gateway – 2 – AUTH-PURCHASE-VERIFY – Hosted Payment Page* document, as appropriate to the integration method). Transaction Result Calls in response to subsequent Void, Capture or Refund API Operations will use this same *merchantNotificationUrl* value that is saved against the original transaction in the EVO Gateway.

If the *merchantNotificationUrl* is not provided in the original transaction, no Transaction Result Call is sent.



1 Transaction Result Call

The Transaction Result Call is sent as a POST server to server call in addition to the Action Response, which is sent to the merchant's client webpage that the customer sees.

The Transaction Result Call is sent to the *merchantNotificationUrl* provided in the Session Token or Action Request.

Transaction Result Calls provide additional information to the Action Response that can be used by the merchant for further reconciliation and information about the transaction.

Parameter	Data Type	Description
merchantId	Integer (18)	The <i>merchantId</i> value received in the Session Token Request of the API Operation
action	String (enum)	The <i>action</i> received in the Session Token Request of the API Operation
merchantTxId	String (50)	The merchant's reference for the transaction provided in the <i>merchantTxId</i> parameter in the API Operation If the <i>merchantTxId</i> parameter was empty or omitted, a value will have been generated by the EVO Gateway as a hexadecimal string
merchantFreeText	String (200)	The free text field contents sent in the in the Session Token Request of the Auth/Purchase/Verify API Operation for the merchant's comments about the transaction
txId	Integer (18)	The unique identifier for the transaction in the EVO Gateway Note: Only returned for a REFUND action
acquirerTxId	String (50)	The transaction identifier in acquirer system, if acquirer returns it
originalTxId	Integer (18)	The EVO Gateway identifier of the original transaction
amount	BigDecimal (15.3)	The total transaction amount, including tax, shipping, surcharge and discount amounts
currency	String (enum)	The ISO alpha-3 code for the currency of the transaction, as defined in the ISO 4217 standard
customerId	String (20)	The merchant's reference for the customer of the transaction provided in the <i>customerId</i> parameter in the API Operation If the <i>customerId</i> parameter was empty or omitted in the Session Token or Action Request, a value will have been generated by the EVO Gateway
pan	String (100)	Customer payment account number (for non-card payments) or EVO Gateway payment card token number used in the transaction
brandId	Integer (18)	The Brand Id used in the transaction, which was supplied by the EVO Gateway when the merchant account was set up in the EVO Gateway
paymentSolutionId	Integer (18)	The EVO Gateway Payment Solution Identifier used in the transaction. The payment solutions that are available to the merchant can be found using the API Operation detailed in the <i>EVO Gateway - 8 - GET AVAILABLE PAYMENT SOLUTIONS</i> document.
status	String (enum)	The transaction status in the EVO Gateway after the API Operation is completed
acquirer	String (100)	For payment cards the acquirer name For non-card payments the payment solution name
acquirerAmount	BigDecimal (15.3)	Amount processed by payment acquirer May be different to <i>amount</i> in the original transaction, especially if the acquirer processed the transaction in a different currency
acquirerCurrency	String (enum)	The ISO alpha-3 currency code, as defined in the ISO 4217 standard , of the currency processed by the payment acquirer, which maybe different to the currency in the original transaction, e.g. if a currency conversion was applied



TRANSACTION RESULT CALL

API Specification

Parameter	Data Type	Description
country	String (enum)	The ISO alpha-2 code country in which the transaction took place, as defined in the ISO 3166 standard
freeText	String (200)	Merchant's free text that was supplied in the <i>freeText</i> field in the original Session Token or Action Request
paymentSolutionDetails	JSON block	For payment cards only: the Transaction Authorisation Code received from the acquirer, format: <pre>{ "authCode": "", "expiryDate": "", "cardType": "", "maskedPan": "", "nameOnCard": "", "avsPostCode": "", "addrResultCode": "" }</pre> Note: the <i>maskedPan</i> value format is "999999*****9999"
rpId	Integer (18)	The identifier for the EVO Gateway Managed Recurring Payment Plan that was requested in the Auth/Purchase/Verify Session Token Request in the 'rp' prefixed parameters If no Plan was requested this field will be empty If there was an error setting up the Plan the errors will be detailed in the <i>errors</i> field
errors	String (400)	Only applies to ERROR transactions It is a brief description of the cause of the error
result	String (enum)	Determines processing result. Possible values: Success Failure Redirection Unknown
resultId	String (36)	Hexadecimal string that is to be used in any support request calls
processingTime	Integer (6)	The time in seconds for the process to complete
additionalDetails	Array	Optional data associated with the transactions. Currently: ageCheck description
customParameter1Or ... customParameter20Or	String (50)	The original 20x (50 character) free text fields provided by the merchant in the Session Token Request of the Auth/Purchase/Verify API Operation
customParameter1 ... customParameter20	String (50)	The 20x (50 character) free text fields provided by the merchant in the Session Token Request of the Auth/Purchase/Verify API Operation with the non-Basic Latin characters replaced by a space character. These values will have been sent for payment processing.